



**QMFZ2.E85783  
Plastics - Component**

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

**Plastics - Component**

[See General Information for Plastics - Component](#)

**LCY CHEMICAL CORP**  
4TH FL 83 SEC 4 BADE RD  
TAIPEI, 105 TAIWAN

E85783

									H	D	
		Min.		H	H	R T I			V	4	C
		Thk	Flame	W	A	Elec	Mech		T	9	T
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I
<b>Polyethylene/Polypropylene (PE/PP), furnished as pellets.</b>											
<b>SJ3032</b>	ALL	0.8	V-0	4	1	65	65	65	0	7	0
		1.6-1.8	V-0	3	0	65	65	65			
<b>Polypropylene (PP), copolymer, "Globalene", furnished as pellets.</b>											
<b>BA(k)5H</b>	ALL	1.0	V-2	4	0	110	110	110	0	6	0
		1.5	V-2	3	0	110	110	110			
		3.0	V-2	2	0	115	115	115			
<b>Polypropylene (PP), mineral reinforced, "Globalene", furnished as pellets.</b>											
<b>73F4-2(@)</b>	NC	1.0	-	-	-	115	115	115	0	5	0
		1.5	HB	3	0	115	115	115			
		3.0	HB	0	0	115	115	115			
<b>Polypropylene (PP), "Globalene", furnished as pellets.</b>											
<b>6(y)24(t)(@)(b)(d)(h)(i)</b>											
	ALL	1.0	HB	4	0	115	115	115	0	5	0
		1.3	HB	3	0	115	115	115			
		1.5	HB	3	0	115	115	115			
		3.0	HB	2	0	115	115	115			
	NC	1.5	HB, RP-89	3	0	115	115	115			
<b>PH286(t)(@) (b)(d)(h)(i)</b>											
	ALL	1.0	HB	4	0	115	115	115	0	5	0
		1.3	HB	3	0	115	115	115			
		1.5	HB	3	0	115	115	115			
		3.0	HB	2	0	115	115	115			
	NC	1.5	HB, RP-89	3	0	115	115	115			
<b>Polypropylene (PP), PP, furnished as pellets.</b>											

<b>SJ3421</b>	ALL	1.5	V-2	-	-	65	65	65	-	-	-
		3.0	V-2	-	-	65	65	65			
<b>Polypropylene (PP), furnished as pellets.</b>											
<b>6331, HP500N</b>	NC	1.5	HB	1	3	65	65	65	0	5	1
		3.0	HB	1	3	65	65	65			
<b>6331-11, 6231-20</b>	ALL	1.5	HB	4	0	65	65	65	0	3	0
		3.2	HB	2	0	65	65	65			
<b>7523, 7533, EP332K, 7633, EP332H</b>											
	ALL	1.5	HB	0	3	115	115	115	0	5	1
		3.0	HB	0	3	115	115	115			
<b>PC366-(Z), HP500J</b>	ALL	1.5	HB	1	2	65	65	65	0	5	1
		3.0	HB	1	2	65	65	65			
<b>PJ3001</b>	ALL	0.75	V-2	3	3	105	105	105	0	4	4
		3.0	V-2	2	2	105	105	105			
<b>PJ3003</b>	ALL	1.5	V-2	-	-	65	65	65	-	-	-
		3.0	V-2	-	-	65	65	65			
<b>PJ3004</b>	ALL	1.5	V-2	3	3	65	65	65	0	4	4
		3.0	V-2	2	2	65	65	65			
<b>PJ3040</b>	ALL	0.8-0.88	V-0	4	0	65	65	65	3	5	0
<b>SH4202</b>	ALL	1.5	HB	3	3	115	115	115	0	5	4
		3.0	HB	2	2	115	115	115			
<b>SI4101</b>	ALL	1.5	HB	4	0	65	65	65	0	3	0
		3.0	HB	3	0	65	65	65			
<b>SJ3003</b>	ALL	0.75	V-2	3	3	65	65	65	0	4	4
		1.5	V-2	3	2	65	65	65			
		3.0	V-2	2	2	65	65	65			
<b>ST031(#), EP332P</b>	NC	1.5	HB	1	2	115	115	115	0	5	1
		3.0	HB	0	2	115	115	115			
<b>ST611K, ST86(x)K</b>	ALL	1.5	HB	4	0	65	65	65	0	4	0
		3.2	HB	2	0	65	65	65			
<b>Random Polypropylene Copolymers, furnished as pellets.</b>											
<b>8(a)81</b>	ALL	1.5	HB	3	0	65	65	65	0	3	0
		3.2	HB	3	0	65	65	65			
<b>8182</b>	ALL	1.5	HB	4	0	65	65	65	0	3	0
		3.2	HB	3	0	65	65	65			
<b>ST86(x)M</b>	ALL	1.5	HB	3	0	65	65	65	0	4	0
		3.0	HB	2	0	65	65	65			

(#) - None or replace by N or H to indicate no nucleating agent were added or the type of nucleating agent.

(@) - May be followed by the letter C.

(a) - Replace by one digit from 6 to 9 and not related to the formulation.

(b) - Subjected to detergents and solutions typically used in fluid containing parts of dishwashing equipment.

(d) - ASTM E-162 (Radiant Panel): Flame spread: less than 125; Sustained flaming: 120 mm; Dripping: Yes.

- (h) - Subjected to detergents, bleach and solutions typically used in fluid containing parts of laundry equipment.
- (i) - Subjected to Simulated Environmental Abrasion Tests per UL 560.
- (k) - Represents the number 1, 2, 3, 4, 5, or 6.
- (t) - May be followed by the letters N, NW, or W.
- (x) - Represents the number 6, 7, 8, 9 or 0 indicating the melt flow rate where 6= 6g/10m, 7= 10g/10m, 8= 16g/10m, 9= 25g/10m and 0= 40g/10m.
- (y) - Represents the number 2, 3, 4, 5, 6, 7, or 8.
- (Z) - Represents the number 3, 4 or 5 indicating the melt flow rate where 3= 3g/10m, 4= 4g/10m, 5= 5g/10m.

Marking: Company name or trademark  ,  ,  and material designation on container, wrapper or finished part.

Last Updated on 2014-04-25

---

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".